

WIDE-APERTURE EXCIPLEX AND EXCIMER LAMPS

APPLICATIONS

- Microelectronics (for photostimulation of sedimentation, cleaning, etc.)
- Ecology (for destruction of harmful organic substances)
- Biology and Medicine (for disinfection)
- For solidification of varnishes and paints

SPECIFICATIONS

Planar excilamps

- | | |
|---------------------------------------------------|-----------------------------------------|
| 1. Wavelength, nm | 126*, 146, 172, 193, 222, 250, 308, 350 |
| 2. Radiant exitance per pulse, kW/cm ² | up to 10 |
| 3. Light beam diameter, cm | 10 |
| 4. Mean output power, mW | up to 200 |

*Output window is supplied by a customer

Coaxial excilamps

- | | |
|--------------------------------------------------|------------------------------|
| 1. Wavelength, nm | 172, 193, 222, 250, 308, 350 |
| 2. Mean output power, W | up to 100 |
| 3. Radiating aperture, cm ² | up to 1000 |

DESIGNERS

V.F. Tarasenko, V.S. Skakun, A.N. Panchenko, E.A. Sosnin, M.I. Lomaev, and E.A. Fomin

MAILING ADDRESS

Laboratory of Optical Radiation of the Institute of High-Current Electronics
of the Siberian Branch of the Russian Academy of Sciences
4, Akademicheskii Prospect, Tomsk 634055, Russia

Phone: (382-2) 25-86-85 or 25-93-44, Fax: (382-2) 25-94-10
Type: 128249 TAKT, E-mail: tarasenko @ loi.hcei.tomsk.su